

What is claimed is:

1. A motor driving system for driving an induction motor with a rotation frequency detector, wherein said induction motor drives a load, and said rotation frequency detector detects a rotation  
5 frequency of said induction motor, comprising:  
a variable speed driving unit connected to said induction motor and having a capacitance at output, wherein said variable speed driving unit rectifies first 3-phase AC power to produce DC power,  
10 and converts the DC power into second 3-phase AC power with a frequency, and drives said induction motor with the second 3-phase AC power; and  
an inverter control unit which generates a frequency instruction and a temporary current  
15 instruction based on said detected rotation frequency and a rotation frequency instruction at least, corrects said temporary current instruction based on at least one of first correction depending on said capacitance and second correction depending on a  
20 predetermined frequency component of said temporary current instruction to produce a current instruction, and controls said variable speed driving unit based on said frequency instruction and said current instruction.
2. The motor driving system according to claim

09988731 "112001  
T0027T"TE88660

1, wherein said variable speed driving unit comprises:

a rectifying unit which rectifies the first  
3-phase AC power in response to said current

5 instruction to produce the DC power; and

a current type inverter having said  
capacitance at the output, wherein said current type  
inverter converts the DC power into the second 3-phase  
AC power with the frequency in response to said

10 frequency instruction.

3. The motor driving system according to claim

1, wherein said inverter control unit comprises:

a first correcting section which corrects  
said temporary current instruction for current flowing  
5 into said capacitance in said first correction to  
produce said current instruction.

4. The motor driving system according to claim

3, wherein said first correcting section corrects said  
temporary current instruction based on a first  
correction factor to produce said current instruction,

5 wherein said first correction factor is

determined based on said capacitor, a self-inductance  
of a stator of said induction motor stator, a mutual  
inductance between the stator and a rotor in said  
induction motor, a self-inductance of the rotor of the

10 induction motor, a resistance of the stator of the

09988731-112001

induction motor, a resistance of the rotor of the induction motor rotor, and slide.

5. The motor driving system according to claim 1, wherein said inverter control unit comprises:

a second correcting section which corrects said temporary current instruction based on a second  
5 correction factor in said second correction to produce said current instruction, wherein said second correction factor is determined such that said predetermined frequency component is set to a predetermined value.

6. The motor driving system according to claim 1, wherein said inverter control unit comprises:

a first correcting section which corrects said temporary current instruction for current flowing  
5 into said capacitance in said first correction to produce a next temporary current instruction; and

a second correcting section which corrects said next temporary current instruction based on a second correction factor in said second correction to  
10 produce said current instruction, wherein said second correction factor is determined such that said predetermined frequency component is set to a predetermined value.

09588731.112001

7. The motor driving system according to claim  
6, wherein said first correcting section corrects said  
temporary current instruction based on a first  
correction factor to produce said next temporary  
5 current instruction,

wherein said first correction factor is  
determined based on said capacitor, a self-inductance  
of a stator of said induction motor stator, a mutual  
inductance between the stator and a rotor in said  
10 induction motor, a self-inductance of the rotor of the  
induction motor, a resistance of the stator of the  
induction motor, a resistance of the rotor of the  
induction motor rotor, and slide.

8. An inverter control apparatus for controlling  
a variable speed driving unit which rectifies first 3-  
phase AC power to produce DC power, and converts the  
DC power into second 3-phase AC power with a frequency  
5 to drive an induction motor, comprising:

a frequency instructing section which  
generates a torque instruction based on a rotation  
frequency of said induction motor and a rotation  
frequency instruction at least and controls the  
10 frequency of the second 3-phase AC power based on said  
torque instruction and the rotation frequency of said  
induction motor; and

a current instructing section which generates

09988731-112001

15 a temporary current instruction from said torque  
instruction, corrects said temporary current  
instruction based on a capacitance and an impedance of  
said induction motor, and controls said variable speed  
driving unit based on said corrected current  
instruction, said variable speed driving unit having  
20 said capacitance at output connected to said induction  
motor.

9. The inverter control apparatus according to  
claim 8, wherein said current instructing section  
further corrects said corrected current instruction  
such that a predetermined frequency component of said  
5 corrected current instruction is set to a  
predetermined value.

10. An inverter control apparatus which outputs a  
control signal to a variable speed driving apparatus  
which drives an induction motor in a variable speed in  
response to said control signal, comprising:

5 a control signal generating section which  
generates said control signal based on a capacitance  
at an output terminal set of said variable speed  
driving apparatus which is connected to said induction  
motor at the output terminal set.

11. The inverter control apparatus according to

09988731.112001

claim 10, wherein said control signal is determined based on parameters associated with a rotor and a stator of said induction motor.

12. The inverter control apparatus according to claim 11, wherein said control signal satisfies the following equation:

$$Idc* = Kc \cdot Id*$$

5 where

Idc\*: said control signal,

Id\*: an auxiliary control signal to be outputted as said control signal when said capacitance is not considered,

10 Kc: a coefficient Kc determined based on a self-inductance of a stator of said induction motor, a mutual inductance between the stator and a rotor of said induction motor, a self-inductance of the rotor of said induction motor, a resistance of the stator of  
15 said induction motor, a resistance of the rotor of said induction motor, and a slide quantity.

13. The inverter control apparatus according to claim 10, wherein said control signal generating section generates said control signal to compensate for a capacitor current flowing into said capacitance.

14. The inverter control apparatus according to

09988731 " 112001

claim 10, wherein said control signal generating section generates said control signal based on a frequency instruction signal to instruct a frequency  
5 of an output of said variable speed driving apparatus, a self-inductance of a stator of said induction motor, a mutual inductance between said stator and a rotor in said induction motor, a self-inductance of said rotor of said induction motor, a resistance of said stator  
10 of said induction motor, a resistance of said rotor of said induction motor, a slide quantity of said induction motor, in addition to said capacitance.

15. An inverter control apparatus which outputs a control signal to a variable speed driving apparatus which drives an induction motor in a variable speed in response to said control signal, comprising:

5 a control signal generating section which generates said control signal based on a frequency component contained in an input signal and a remaining frequency components of said input signal.

16. The inverter control apparatus according to claim 15, wherein said control signal generating section multiplies said input signal and a reciprocal of a ratio of said frequency component to said input  
5 signal and generates said control signal based on the multiplication result.

09988731.112001

17. An inverter control apparatus which outputs a control signal to a variable speed driving apparatus which drives an induction motor in a variable speed in response to said control signal, comprising:

5 a capacitor correction signal generating section which generates a capacitor correction signal based on a capacitance connected with an output terminal set of said variable speed driving apparatus; and

10 a control signal generating section which generates said control signal based on an inverter frequency component contained in said capacitor correction signal and a remaining frequency component of said capacitor correction signal other than said  
15 inverter frequency component.

18. A motor driving system comprising:

a variable speed driving apparatus which supplies an AC control power generated based on a control signal to an AC motor to drive said AC motor  
5 in variable speed; and

an inverter control apparatus which outputs said control signal to said variable speed driving apparatus,

wherein said variable speed driving apparatus  
10 comprises:

a rectification section which rectifies AC

09988731-112001



power to generate DC power; and

an inverter section which generates said AC control power from said generated DC power,

- 15           said inverter control apparatus generates said control signal based on a capacitance connected with an output terminal set of said variable speed driving apparatus, an inverter frequency component of an input signal and a remaining frequency component of
- 20   said input signal other than said inverter frequency component, and outputs said control signal to said rectification section.

09988731 "112001  
T0021T" TE78860